

Product data sheet

Specifications



Capacitor contactor, TeSys Deca, 63 kVAR at 400 V/50 Hz, coil 220 V AC 50/60 Hz

LC1DWK12M7

Product availability : Stock - Normally stocked in distribution facility

Price* : 1,550.00 USD

Main

Range	TeSys
Product name	TeSys LC1D.K TeSys Deca
Product or Component Type	Capacitor duty contactor
Device short name	LC1DWK
Device Application	Control
Contactor application	Power factor correction
Utilisation category	AC-6b
Poles description	3P
Power pole contact composition	3 NO
[Ue] rated operational voltage	Power circuit 690 V AC 50/60 Hz
Reactive power rating	35 kvar 230 V AC 50 Hz 140 °F (60 °C) 63 kvar 400 V AC 50 Hz 140 °F (60 °C) 67 kvar 440 V AC 50 Hz 140 °F (60 °C) 104 kvar 690 V AC 50 Hz 140 °F (60 °C) 30 kvar 230 V AC 60 Hz 140 °F (60 °C) 60 kvar 460 V AC 60 Hz 140 °F (60 °C) 80 kvar 575 V AC 60 Hz 140 °F (60 °C)
Control circuit type	AC 50/60 Hz
[Uc] control circuit voltage	220 V AC 50/60 Hz
Auxiliary contact composition	1 NO + 2 NC instantaneous
Electrical durability	300000 cycles 400 V 200000 cycles 690 V
Mounting Support	DIN rail Plate
Standards	EN/IEC 60947-1 EN/IEC 60947-4-1 UL 60947-4-1 CSA C22.2 No 60947-4-1
Product Certifications	IECEE CB Scheme UL CSA UKCA
Connections - terminals	Control circuit screw clamp terminals 1 0.00...0.01 in ² (1...4 mm ²) solid Control circuit screw clamp terminals 2 0.00...0.01 in ² (1...4 mm ²) solid Control circuit screw clamp terminals 1 0.00...0.01 in ² (1...4 mm ²) flexible without cable end Control circuit screw clamp terminals 2 0.00...0.01 in ² (1...4 mm ²) flexible without cable end Control circuit screw clamp terminals 1 0.00...0.01 in ² (1...4 mm ²) flexible with cable end Control circuit screw clamp terminals 2 0.00...0.00 in ² (1...2.5 mm ²) flexible with cable end Power circuit connector 1 0.01...0.08 in ² (4...50 mm ²) solid

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Power circuit connector 2 0.01...0.04 in² (4...25 mm²) solid
Power circuit connector 1 0.01...0.08 in² (4...50 mm²) flexible without cable end
Power circuit connector 2 0.01...0.04 in² (4...25 mm²) flexible without cable end
Power circuit connector 1 0.01...0.08 in² (4...50 mm²) flexible with cable end
Power circuit connector 2 0.01...0.02 in² (4...16 mm²) flexible with cable end

Tightening torque	Power circuit 79.66 lbf.in (9 N.m) connector Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals
--------------------------	--

Maximum operating rate	240 cyc/h
-------------------------------	-----------

Complementary

Auxiliary contacts type	Mechanically linked 1 NO + 2 NC IEC 60947-5-1
--------------------------------	---

Environment

IP degree of protection	IP20 front face IEC 60529
--------------------------------	---------------------------

Ambient Air Temperature for Operation	23...140 °F (-5...60 °C)
--	--------------------------

Ambient Air Temperature for Storage	-76...176 °F (-60...80 °C)
--	----------------------------

Operating altitude	0...9842.52 ft (0...3000 m)
---------------------------	-----------------------------

Height	7.09 in (180 mm)
---------------	------------------

Width	3.35 in (85 mm)
--------------	-----------------

Depth	6.06 in (154 mm)
--------------	------------------

Net Weight	3.64 lb(US) (1.65 kg)
-------------------	-----------------------

Ordering and shipping details

Category	22359-CTR, TESYS D, OPEN, 80-150A AC&DC
-----------------	---

Discount Schedule	I12
--------------------------	-----

GTIN	3389110060539
-------------	---------------

Nbr. of units in pkg.	1
------------------------------	---

Package weight(Lbs)	3.79 lb(US) (1.721 kg)
----------------------------	------------------------

Returnability	No
----------------------	----

Country of origin	CZ
--------------------------	----

Packing Units

Unit Type of Package 1	PCE
-------------------------------	-----

Package 1 Height	5.12 in (13.0 cm)
-------------------------	-------------------

Package 1 width	6.69 in (17.0 cm)
------------------------	-------------------

Package 1 Length	7.48 in (19.0 cm)
-------------------------	-------------------

Unit Type of Package 2	P06
-------------------------------	-----

Number of Units in Package 2	48
-------------------------------------	----

Package 2 Weight	199.76 lb(US) (90.608 kg)
-------------------------	---------------------------

Package 2 Height	29.53 in (75.0 cm)
-------------------------	--------------------

Package 2 width	31.50 in (80.0 cm)
------------------------	--------------------

Package 2 Length	23.62 in (60.0 cm)
-------------------------	--------------------

Offer Sustainability

Sustainable offer status	Green Premium product
---------------------------------	-----------------------

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
-----------------	-----------