



Accessory 3WA/3WL instantaneous (0,08 s) and short-delay (0,2 s), 208-240 V AC / 220-250 V DC,

Model			
product brand name	SENTRON		
product designation	3WA circuit breaker accessories		
design of the product	undervoltage release (UVR), instantaneous (0.08 s) and short-time delayed (0.2 s), 208 to 240 V AC / 220 to 250 V DC		
closing apparent power [VA]	50 VA		
operating apparent power [VA]	5 VA		
closing active power [W]	50 W		
operating active power [W]	5 W		
OFF-delay time / minimum	80 ms		
OFF-delay time / maximum	200 ms		
opening time / of circuit breaker / at $U_s = 0\%$	73 ms		
control supply voltage (U_s) / at AC / rated value	208 to 240 V 50/60 Hz		
design of the DIAZED fuse link gG/miniature circuit breaker with tripping characteristic class C 100% / for short-circuit protection / minimum permissible	1 A		
ambient temperature / during operation			
• minimum	-40 °C		
• maximum	70 °C		
ambient temperature / during storage			
• minimum	-40 °C		
• maximum	80 °C		
General Product Approval	EMC	Declaration of Conformity	Marine / Shipping

[Confirmation](#)



Dangerous Good

[Transport Information](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WA9111-0AE06>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3WA9111-0AE06>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WA9111-0AE06

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



