



Accessory 3WA/3WL Charging Motor (M) 208-240 V AC / 220-250 V DC

Model	
product brand name	SENTRON
product designation	3WA circuit breaker accessories
design of the product	MO spring charging motor
type of the driving mechanism	motorized operating mechanism
operating apparent power [VA]	135 VA
electrical endurance (switching cycles)	25 000
operating frequency / maximum	60 1/h
time for clamping / of the spring energy store / with control supply voltage (Us)	10 s
control supply voltage / at DC / rated value / maximum	250 V
design of the DIAZED fuse link gG / for short-circuit protection / minimum permissible	2 A
ambient temperature / during operation	
• minimum	-40 °C
• maximum	70 °C
ambient temperature / during storage	
• minimum	-40 °C
• maximum	80 °C
General Product Approval	EMC
Declaration of Conformity	
Marine / Shipping	

[Confirmation](#)



Dangerous Good

[Transport Information](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3WA9111-0AF06>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3WA9111-0AF06>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WA9111-0AF06

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



