



Miniature circuit breaker 415 V 10kA, 2-pole, C, 25A

Model	
product brand name	SENTRON
product designation	Miniature circuit breaker
General technical data	
number of poles	2
design of pole	2P
tripping characteristic class	C
mechanical service life (switching cycles) / typical	10 000
overvoltage category	III
degree of pollution	2
Voltage	
type of voltage / of the operating voltage	AC
insulation voltage (Ui)	
• with single-phase operation / at AC / rated value	250 V
• with multi-phase operation / at AC / rated value	440 V
Supply voltage	
supply voltage / at AC / rated value	415 V
value range / of the supply voltage frequency	50/60 Hz
operating voltage	
• with multi-phase operation / at AC / maximum	440 V
• at DC / rated value / maximum	72 V
Protection class	
protection class IP	IP20, with connected conductors
Switching capacity	
switching capacity current	
• according to EN 60898 / rated value	10 kA
energy limitation class	3
Dissipation	
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	2.92 W
Current	
operational current	
• at 30 °C / rated value	25 A
• at AC / rated value	25 A
suitability for operation	Residential buildings/infrastructure
Product details	
product feature	
• halogen-free	Yes
• sealable	Yes

• silicon-free	Yes		
product extension / installable / supplementary devices	Yes		
Connections			
connectable conductor cross-section / solid			
• minimum	0.75 mm ²		
• maximum	25 mm ²		
connectable conductor cross-section / stranded			
• minimum	0.75 mm ²		
• maximum	25 mm ²		
connectable conductor cross-section / finely stranded / with core end processing			
• minimum	0.75 mm ²		
• maximum	25 mm ²		
tightening torque / with screw-type terminals			
• minimum	2.5 N·m		
• maximum	3 N·m		
Mechanical Design			
height	90 mm		
width	18 mm		
depth	76 mm		
installation depth	70 mm		
number of modular width units	1		
mounting position	any		
net weight	310 g		
Environmental conditions			
ambient temperature / during operation			
• minimum	-25 °C		
• maximum	55 °C		
ambient temperature / during storage			
• minimum	-40 °C		
• maximum	75 °C		
Certificates			
reference code			
• according to EN 61346-2	F		
• according to IEC 81346-2	F		
General Product Approval	Declaration of Conformity	Test Certificates	other

[Confirmation](#)



[Miscellaneous](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SL4225-7RC>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SL4225-7RC>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SL4225-7RC

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



