

wall-mounting enclosure polyester monobloc IP66 H647xW436xD250mm

Local distributor code: 403422748 NSYPLM64G

EAN Code: 3606480776632

Main

Range	Thalassa
Product name	Thalassa PLM
Device short name	PLM
Enclosure type	Multi-purpose
Category	Compact enclosure
Nominal height	647 mm
Nominal width	436 mm
Nominal depth	250 mm
Enclosure mounting	Wall mounted
Device composition	1 body 1 door 2 lock
Door type	Plain
Lock type	3 mm double-bar lock

Complementary

Number of locks	2
Mounting plate description	Without mounting plate
Accessibility for operation	Front
Removable parts	Door by hinges
Material	Polyester reinforced with fibreglass
Colour	Grey (RAL 7035)
Standards	NEMA classification 13 NEMA classification 4X IEC 62208
Product certifications	UL
Electrical insulation class	Class II

Environment

IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262

Fire resistance	960 °C conforming to IEC 62208
Ambient air temperature for operation	-4080 °C
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	12.341 kg
Package 1 Height	27.5 cm
Package 1 width	46.0 cm
Package 1 Length	71.0 cm
Offer Sustainability Sustainable offer status	Green Premium product
Sustainable offer status	Green Premium product REACh Declaration
Sustainable offer status REACh Regulation	
	REACh Declaration
Sustainable offer status REACh Regulation REACh free of SVHC EU RoHS Directive	Yes Pro-active compliance (Product out of EU RoHS legal scope)
Sustainable offer status REACh Regulation REACh free of SVHC EU RoHS Directive Mercury free	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Sustainable offer status REACh Regulation REACh free of SVHC	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration Yes

Contractual warranty

18 months

Warranty