

ConneXium Premium Unmanaged Switch - 7 ports for copper + 2 ports for fiber optic single-mode

TCSESPU093F2CS0

| | ١ | V | 1 | 2 | ı | n |
|---|---|---|---|---|---|---|
| ı | J | v | u | ч | u | |

| Range of product | ConneXium |
|---------------------------------------|--|
| Product or component type | Ethernet TCP/IP unmanaged switch |
| Concept | Transparent Ready |
| Communication port protocol | Ethernet TCP/IP |
| Port Ethernet | 10/100BASE-TX - 7 port(s) copper cable 100BASE-FX - 2 port(s) fiber optic |
| Maximum number of switches in cascade | Unlimited |

| Complementary | |
|--|--|
| Integrated connection type | Shielded RJ45 copper cable Duplex SC fiber optic |
| Transmission support medium | Twisted shielded pairs cable CAT 5E for copper cable Single mode optical fiber for fiber optic |
| Maximum cable distance between devices | 100 m copper cable |
| Optic fiber length | 32.5 km 9/125 μm |
| Attenuation | 016 dB (9/125 μm) |
| Ethernet service | Multicast filtering Data stream control |
| Communication service | Quality of Service (QoS) |
| [Us] rated supply voltage | 1224 V |
| Supply voltage limits | 9.632 V DC SELV |
| Power consumption in W | 6.9 W |
| Electrical connection | Removable connector 6 ways power supply |
| Mounting support | 35 mm symmetrical DIN rail |
| Marking | CE UL RCM |
| Local signalling | 1 dual colour LED (green/yellow) for P1 P2 power supplies 1 LED per channel (yellow) for data rate (ETH LINK) 1 dual colour LED (green/yellow) for link status |
| Ethernet cabling system | TF switches |
| Width | 56 mm |
| Height | 135 mm |

Life Is On Schneider

| Depth | 117 mm | |
|------------|----------|--|
| Net weight | 0.510 kg | |
| | | |

Environment

| Ambient air temperature for operation | -4070 °C |
|---------------------------------------|--|
| Relative humidity | 1095 % non-condensing |
| IP degree of protection | IP40 |
| Directives | 2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility |
| Standards | UL 61010 EN/IEC 61131 |
| Product certifications | CE UL RCM |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|---------|
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 801.0 g |
| Package 1 Height | 13.5 cm |
| Package 1 width | 16.2 cm |
| Package 1 Length | 23.5 cm |
| Unit Type of Package 2 | S04 |
| Number of Units in Package 2 | 8 |
| Package 2 Weight | 6.56 kg |
| Package 2 Height | 30.0 cm |
| Package 2 width | 40.0 cm |
| Package 2 Length | 60.0 cm |

Contractual warranty

| Warranty 18 months | |
|--------------------|--|
|--------------------|--|

Product data sheet

TCSESPU093F2CS0

Dimensions Drawings

Dimensions

