



Acti 9 - fuse-disconnector STI - 1 pole - 25 A - for fuse 10.3 x 38 mm

A9N15636

Range	Acti 9
Product name	Acti9 STI
Product or component type	Fuse-disconnector
Device short name	STI
Poles description	1P

Complementary	
[In] rated current	2 A
	4 A
	6 A
	10 A
	16 A
	20 A
	25 A
Fuse curve	AM
	GG
Fuse size	10.3 x 38 mm
[Ue] rated operational voltage	500 V AC
[Ui] rated insulation voltage	500 V AC 50/60 Hz
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	75 mm
Colour	White
Connections - terminals	Screw clamp terminals1 cable(s) 0.7510 mm² rigid
Connections - terminals	Screw clamp terminals1 cable(s) 0.56 mm² flexible
	Screw clamp terminals? cable(s) 0.754 mm² rigid
	Screw clamp terminals2 cable(s) 0.56 mm² flexible
Wire stripping length	12 mm

Environment

Tightening torque

Standards IEC 60269-1/2

2 N.m

IP degree of protection	IP20
Pollution degree	3
Ambient air temperature for operation	-2060 °C
Ambient air temperature for storage	-4080 °C

Packing Units

3	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	54.5 g
Package 1 Height	7.8 cm
Package 1 width	1.8 cm
Package 1 Length	8.4 cm
Unit Type of Package 2	P12
Number of Units in Package 2	1152
Package 2 Weight	84.4 kg
Package 2 Height	45.0 cm
Package 2 width	80.0 cm
Package 2 Length	120.0 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	12
Package 3 Weight	710.0 g
Package 3 Height	8.6 cm
Package 3 width	9.4 cm
Package 3 Length	22.2 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

Contractual warranty

Warranty 12 months
