

insulation monitoring module, ComPact NSX 100/160/250, 200 VAC to 440 VAC 50/60 Hz, 0.1 A to 1 A, 3 poles

LV429459

① Discontinued on: 07 February 2022

① Discontinued

Main	
Product or component type	Insulation monitoring device
Device application	Insulation
Range compatibility	ComPact NSX100 ComPact NSX160 ComPact NSX250

Poles description 3P

Complementary

[Ue] rated operational voltage	200440 V
Network type	AC
Network frequency	50/60 Hz
Measurement accuracy	-50 %0 %
Residual earth-leakage sensitity adjustment type	Adjustable
[l∆n] residual earth-leakage sensitive adjustment	0.1 A 0.2 A 0.5 A 1 A
[Δt] residual earth-leakage time delay adjustment	510 s

Environment

IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK04 conforming to IEC 62262

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.09 kg
Package 1 Height	14.5 cm
Package 1 width	15.0 cm
Package 1 Length	18.0 cm

Unit Type of Package 2	S03
Number of Units in Package 2	8
Package 2 Weight	9.207 kg
Package 2 Height	30.0 cm
Package 2 width	30.0 cm
Package 2 Length	40.0 cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Contractual warranty

Warranty	18 months
vvairanty	10 months

Recommended replacement(s)

LV429459 is replaced by:



Earth-leakage add-on alarm module VigiPacT, ComPacT NSX 100/160/250, 200VAC to 440VAC, 30mA to 30A, 3 poles

LV429498