

## FICHA TECNICA

**Producto** : Selector M-O-A  
**Marca** : Salzer  
**Modelo** : S16-61025  
**Amps** : 16A  
**Polos** : 1  
**Certificac.** :



AC Rating Code	Unit	S16/TP16/ RT16
Rated Operational Voltage(Ue)	V	690
Rated frequency	Hz	50/60
Rated impulse withstand Voltage(Uimp)	Kv	6
Rated Operational Current(Ie) AC21/AC1	A	16
Rated Uninterrupted Current (Ith)	A	20
Rated Operational Power		
AC23A *3 Ph , 415 V"	KW	7.5
	A	13
AC3	KW	5.5
"3 Ph , 415 V"	A	10
Short Circuit Capacity		
Rated Fuse Short Circuit Current	KA	5
Fuse Size (Type gG/gM)	A	16
Terminal Cross Section		
Single / Multiple	min	mm <sup>2</sup> 1.5
	max	mm <sup>2</sup> 4
Fine strand	min	mm <sup>2</sup> 1
	max	mm <sup>2</sup> 2.5
Terminal Cross Section	Metric	M3.5
Terminal Tightening Torque	Nm	0.8

### CSA/UL Ratings

AC Rating Code	Unit	S16 TP16 RT16
<b>Ampere Rating</b>	A	15
Operational Voltage	V	600
HP Rating 1 Phase	HP	0.33
	HP	1
3 Phase	HP	1.5
	HP	3
	HP	3
	HP	5

