

FICHA TECNICA

Producto : Selector voltimetrico
Marca : Salzer
Modelo : S16-61312
Amps : 16A
Polos : 1
Certificac. :




AC Rating Code	Unit	S16/TP16/ RT16
Rated Operational Voltage(Ue)	V	690
Rated frequency	Hz	50/60
Rated impulse withstand Voltage(Uimp)	Kv	6
Rated Operational Current(Ie) AC21/AC1	A	16
Rated Uninterrupted Current (Ith)	A	20
Rated Operational Power		
AC23A "3 Ph , 415 V"	KW	7.5
	A	13
AC3	KW	5.5
"3 Ph , 415 V"	A	10
Short Circuit Capacity		
Rated Fuse Short Circuit Current	KA	5
Fuse Size (Type gG/gM)	A	16
Terminal Cross Section		
Single / Multiple	min	mm ² 1.5
	max	mm ² 4
Fine strand	min	mm ² 1
	max	mm ² 2.5
Terminal Cross Section	Metric	M3.5
Terminal Tightening Torque	Nm	0.8

CSA/UL Ratings


AC Rating Code	Unit	S16 TP16 RT16
Ampere Rating	A	15
Operational Voltage	V	600
HP Rating 1 Phase 120V	HP	0.33
240V	HP	1
3 Phase 120V	HP	1.5
240V	HP	3
480V	HP	3
600V	HP	5

61312



90 Degree

Connecting Diagram



SELECTOR VOLTIMETRICO 3 FASES LINEA A LINEA

