FICHA TECNICA

Producto Conmutador 1-0-2

Marca Salzer Modelo S32-61026

Amps 32A Polos 2

LISTED SIECE CE Certificac.



AC Rating Code		Unit	S32 RT32
Rated Operational Voltage(Ue)		V	690
Rated frequency		Hz	50/60
Rated impulse withstand Voltage(Uimp)		Kv	6
Rated Operational Current(le) AC21/AC1		Α	32
Rated Uninterrupted Current (Ith)		Α	40
Rated Operational Power			
AC23A "3 Ph , 415 V"		KW	15
		A	26
AC3		KW	11
"3 Ph , 415 V"		A	19
Short Circuit Capacity			
Rated Fuse Short Circuit Current		KA	10
Fuse Size (Type gG/gM)		Α	32
Terminal Cross Section			
Single / Multiple	min	mm²	2.5
	max	mm²	6
Fine strand	min	mm²	1.5
	max	mm²	4
Terminal Cross Section		Metric	M4
Terminal Tightening Torque		Nm	1.2



AC Rating Code	Unit	S32 RT32
Ampere Rating	А	30
Operational Voltage	V	600
HP Rating 1 Phase 120V	HP	1.5
240V	HP	3
3 Phase 120V	HP	3
240V	HP	7.5
480V	HP	10
600V	HP	15





