

# FICHA TECNICA

Producto : Conmutador 1-0-2  
 Marca : Salzer  
 Modelo : S32-61028  
 Amps : 32A  
 Polos : 4  
 Certificac. : 



S25-61028  
S32-61028

AC Rating Code	Unit	S32 RT32
Rated Operational Voltage(Ue)	V	690
Rated frequency	Hz	50/60
Rated impulse withstand Voltage(Uimp)	Kv	6
Rated Operational Current(Ie) AC21/AC1	A	32
Rated Uninterrupted Current (Ith)	A	40
Rated Operational Power		
AC23A *3 Ph , 415 V"	KW	15
	A	26
AC3	KW	11
*3 Ph , 415 V"	A	19
Short Circuit Capacity		
Rated Fuse Short Circuit Current	KA	10
Fuse Size (Type gG/gM)	A	32
Terminal Cross Section		
Single / Multiple	min	mm <sup>2</sup> 2.5
	max	mm <sup>2</sup> 6
Fine strand	min	mm <sup>2</sup> 1.5
	max	mm <sup>2</sup> 4
Terminal Cross Section	Metric	M4
Terminal Tightening Torque	Nm	1.2

## CSA/UL Ratings

AC Rating Code	Unit	S32 RT32
<b>Ampere Rating</b>	A	30
Operational Voltage	V	600
HP Rating 1 Phase	HP	1.5
240V	HP	3
3 Phase	HP	3
240V	HP	7.5
480V	HP	10
600V	HP	15

