

## FICHA TECNICA

**Producto** : Conmutador 1-0-2  
**Marca** : Salzer  
**Modelo** : S40-61028  
**Amps** : 40A  
**Polos** : 4  
**Certificac.** :    



AC Rating Code	Unit	S40 RT40
Rated Operational Voltage(Ue)	V	690
Rated frequency	Hz	50/60
Rated impulse withstand Voltage(Uimp)	Kv	6
Rated Operational Current(Ie) AC21/AC1	A	40
Rated Uninterrupted Current (Ith)	A	50
Rated Operational Power		
AC23A "3 Ph , 415 V"	KW	18.5
	A	32
AC3	KW	15
"3 Ph , 415 V"	A	26
Short Circuit Capacity		
Rated Fuse Short Circuit Current	KA	20
Fuse Size (Type gG/gM)	A	40
Terminal Cross Section		
Single / Multiple	min	mm <sup>2</sup> 2.5
	max	mm <sup>2</sup> 10
Fine strand	min	mm <sup>2</sup> 2.5
	max	mm <sup>2</sup> 6
Terminal Cross Section	Metric	M5
Terminal Tightening Torque	Nm	2

### CSA/UL Ratings

AC Rating Code	Unit	S40
<b>Ampere Rating</b>	A	40
Operational Voltage	V	600
HP Rating 1 Phase 120V	HP	2
240V	HP	5
3 Phase 120V	HP	5
240V	HP	10
480V	HP	20
600V	HP	24

