



Representative Image

Ref. No. 666104 | Cat. No. CLSQ31D
Description: CLASSIC analogue time switch+quartz synchron 1CO day 130vdc/230Vac
EAN 5413656661047
Home > Modular DIN-rail devices > Comfort functions > Time switches
Descriptors

Category	Time switches
----------	---------------

Specifications

Product type	Analogue time switches
Series	Classic
Range	Analogue time switch - Classic
Type	Day programmable (1x24x2)
Synchronisation	kwarts
AC/DC	AC/DC
Nominal current	16A/250Vac
Number of channels	1CO
Number of modules	3
Standards	CE, EN-60730-1, EN-60730-2-7, VDE 0633
Control system Control voltage range	130 Vdc/230 Vca
Control system Power consumption (W)	1 VA
Control system Screws	Pozidriv 1
Clockwork Operating voltage	230Vac - 130Vdc
Clockwork Accuracy	±2.5s/day by 20°C
Clockwork Sealable	Yes
Clockwork Screws	Pozidriv 1
Contact	Voltage-free change over
Rated switching capacity- resistive load	16A/250Vac
Rated switching capacity- inductive load	4A/250Vac
Rated switching capacity- incandesc lamps (W)	1350 W
Shortest switching time	30 min
Shortest switching time day-program	30 min
Shortest switching time week-program	3 h
Screws	Pozidriv 1
Clockwork Operating temp range (°C)	-20°C / +55°C
Operating voltage	230Vac - 130V dc
On/Off/Auto switch	Yes
Clockwork Consumption at 230 Vac	1 VA

Specifications

Clockwork Battery backup	150 h
Clockwork Battery charging time	70 h
Terminal capacity min (mm ²)	1x0.5 mm ²
Terminal capacity max (mm ²)	1x6 mm ² / 2x2.5 mm ²
Clockwork Term cap min	1x0.5 mm ²
Clockwork Term cap max	1x6 mm ² or 2x2.5 mm ²

Classifications

ETIM 5.0	EC002304 - Analogous time switch for distribution board
ETIM 6.0	EC002304 - Analogous time switch for distribution board
ETIM 7	EC002304 - Analogous time switch for distribution board

Dimensions

Weight	0.170 kg
--------	----------

Package Information

Standard packing	1
------------------	---